



DISCUSSION

Precast concrete, steel-braced, hybrid pipe rack structures

Regarding “Precast Concrete, Steel-Braced, Hybrid Pipe Rack Structures”¹ by Sebastián F. Vaquero, Damián R. Correa, and Sergio F. Wolkomirski in the Fall 2013 issue of *PCI Journal*, how will the socket fixing of the column avoid brittle failure at the socket joint?

Devendra Joshi

Authors' response

As stated in *NEHRP Recommended Seismic Provisions for New Buildings and Other Structures*,² FEMA P-750 2009 edition: “Most structural systems have some components or limit states that cannot provide reliable inelastic response or energy dissipation. Such components or limit states must be designed considering that the actual forces in the structure will be larger than those at first significant yield. The standard specifies an overstrength factor, Ω_o , to amplify the prescribed forces for use in design of such components or limit states. This specified overstrength factor is neither an upper nor a lower bound; it is simply an approximation specified to provide a nominal degree of protection against undesirable behavior.”

Having this concept in mind, we designed the socket foundation to remain elastic by using the seismic load effect with an overstrength factor Ω_o of 3.0 (transverse direction) and 2.5 (longitudinal direction).

Sebastián F. Vaquero

Research engineer and assistant professor, Structural Engineering Department, University of Buenos Aires
Buenos Aires, Argentina

Damián R. Correa

Professor, Structural Engineering Department, University of Buenos Aires
Buenos Aires, Argentina

Sergio F. Wolkomirski

Co-owner, Fontan Balestra & Associates
Buenos Aires, Argentina

References

1. Vaquero, Sebastián F., Damián R. Correa, and Sergio F. Wolkomirski. 2013. "Precast Concrete, Steel-Braced, Hybrid Pipe Rack Structures." *PCI Journal* 58 (4): 55–67.
2. Building Seismic Safety Council of the National Institute of Building Sciences. 2009. *NEHRP Recommended Seismic Provisions for New Buildings and Other Structures*. FEMA P-750. Washington, DC: Federal Emergency Management Agency. [\[1\]](#)

ERRATA

On page 98 under "Specimen Design and Construction" in "Comparison of Details for Controlling End-Region Cracks in Precast, Pretensioned Concrete I-Girders" in the Spring 2014 issue of *PCI Journal*, it should read " ... specimen LB had 27% more end reinforcement by area than CT." on page 106: last line it states: ...specimen LB had 27% more end-region reinforcement than the control specimen....."

In Fig. 10 on page 121 of "Analytical Investigation and Monitoring of End-Zone Reinforcement of the Alaskan Way Viaduct Super Girders" in the Spring 2014 issue of *PCI Journal*, the top dimension should be " $h/2$."

We regret the errors.

COMMENTS?

The editors welcome discussion of the technical content of *PCI Journal* papers. Comments must be confined to the scope of the paper to which they respond and should make a reasonable and substantial contribution to the discussion of the topic. Discussion not meeting this requirement will be returned or referred to the authors for private reply.

Discussion should include the writer's name, title, company, city, and email address or phone number and may be sent to the respective authors for closure. All discussion becomes the property of *PCI Journal* and may be edited for space and style. Discussion is generally limited to 1800 words with each table or illustration counting as 300 words. Follow the style of the original paper, and use references wherever possible without repeating available information.

The opinions expressed are those of the writers and do not necessarily reflect those of PCI or its committees or councils.

All discussion of papers in this issue must be received by September 1, 2014. Please address reader discussion to *PCI Journal* at journal@pci.org.