


Strand Pattern Designation




Safe loads shown include dead load of 10 psf for untopped members and 15 psf for topped members. Remainder is live load. Long-time cambers include superimposed dead load but do not include live load.

Capacity of selections of other configurations are similar. For precise values, see local hollow-core manufacturer.

HOLLOW-CORE

4'-0" x 8"
Normal Weight Concrete



$f'_c = 5,000$ psi
 $f'_{ci} = 3,500$ psi

Section Properties

	Untopped	Topped
A	= 215 in. ²	—
I	= 1,666 in. ⁴	3,071 in. ⁴
y_b	= 4.00 in.	5.29 in.
y_t	= 4.00 in.	4.71 in.
Z_b	= 416 in. ³	580 in. ³
Z_t	= 416 in. ³	652 in. ³
b_w	= 12.00 in.	12.00 in.
wt	= 224 plf	324 plf
	56 psf	81 psf
V/S	= 1.92 in.	

Key

- 335 — Safe superimposed service load, psf
- 0.2 — Estimated camber at erection, in.
- 0.3 — Estimated long-time camber, in.

4HC8

Table of safe superimposed service load (psf) and cambers

No Topping

Strand Designation Code	Span, ft.																							
	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	
66-S	335	286	246	213	185	162	141	124	109	96	85	75	66	58	50	44	38	33						
	0.2	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.1	0.0	-0.1	-0.2	-0.2	-0.3	-0.5	-0.7			
76-S	375	337	291	252	220	193	170	150	133	118	105	93	83	73	65	58	51	45	39	34				
	0.2	0.3	0.3	0.3	0.3	0.3	0.4	0.4	0.4	0.4	0.3	0.3	0.3	0.3	0.2	0.1	0.0	-0.1	-0.2	-0.4	-0.6	-0.8		
58-S	372	342	317	296	275	255	225	200	179	160	143	128	115	104	93	84	76	68	61	55	49	44	39	
	0.3	0.3	0.4	0.4	0.5	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.5	0.5	0.4	0.3	0.2	0.1	0.0	-0.1	
	0.4	0.5	0.5	0.6	0.6	0.6	0.7	0.7	0.7	0.7	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.6	0.5	0.4	
68-S		351	326	302	284	266	250	236	218	196	176	159	143	130	117	107	97	88	80	72	65	59	54	
		0.4	0.5	0.5	0.6	0.6	0.7	0.7	0.7	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.7	0.7	0.6	0.5	0.4	
		0.6	0.6	0.7	0.8	0.8	0.9	0.9	0.9	1.0	1.0	1.0	1.0	1.0	0.9	0.9	0.8	0.7	0.6	0.4	0.2	0.0	-0.2	
78-S		360	335	311	290	272	256	242	229	215	205	188	170	154	141	128	117	106	97	89	81	74	67	
		0.5	0.6	0.6	0.7	0.7	0.8	0.9	0.9	1.0	1.0	1.0	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.0	0.9	0.9	
		0.7	0.8	0.8	0.9	1.0	1.0	1.1	1.2	1.2	1.3	1.3	1.3	1.3	1.3	1.3	1.2	1.2	1.1	1.0	0.9	0.7	0.5	

4HC8 + 2

Table of safe superimposed service load (psf) and cambers

2" Normal Weight Topping

Strand Designation Code	Span, ft.																							
	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	
66-S	309	267	231	201	175	153	133	117	102	89	77	67	55	44	33									
	0.2	0.2	0.2	0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.1	0.0	0.0	-0.1									
	0.2	0.2	0.2	0.2	0.2	0.1	0.1	0.0	-0.1	-0.2	-0.3	-0.4	-0.6	-0.7	-0.9									
76-S		316	275	241	211	185	163	144	127	112	99	87	74	62	50	40	31							
		0.3	0.3	0.3	0.3	0.4	0.4	0.4	0.3	0.3	0.3	0.3	0.2	0.2	0.1	0.0	-0.1							
		0.3	0.3	0.3	0.3	0.2	0.2	0.2	0.1	0.0	-0.1	-0.2	-0.4	-0.5	-0.7	-0.9	-1.2							
58-S			352	317	279	248	220	196	174	156	139	124	111	98	84	71	60	50	40	32				
			0.5	0.5	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.5	0.5	0.5	0.5	0.4	0.3	0.2	0.1	0.0				
			0.5	0.5	0.5	0.5	0.5	0.4	0.4	0.3	0.3	0.2	0.1	-0.1	-0.2	-0.4	-0.6	-0.9	-1.2	-1.5				
68-S				337	316	297	268	239	215	193	173	156	141	127	114	100	87	75	64	54	45	36		
				0.6	0.7	0.7	0.7	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.8	0.7	0.6	0.5	0.4	0.2		
				0.6	0.6	0.7	0.7	0.7	0.6	0.6	0.6	0.5	0.4	0.3	0.2	0.0	-0.2	-0.4	-0.6	-0.9	-1.2	-1.6		
78-S					346	325	306	286	271	252	227	205	186	168	152	138	124	111	98	86	76	66	56	47
					0.7	0.8	0.9	0.9	1.0	1.0	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.0	0.9	0.9	0.7	0.6	
					0.8	0.8	0.8	0.9	0.9	0.9	0.9	0.9	0.8	0.8	0.7	0.6	0.5	0.3	0.1	-0.1	-0.3	-0.6	-0.9	-1.3

Strength based on strain compatibility; bottom tension limited to $6\sqrt{f'_c}$; see pages 2-3-2-6 for explanation.