3.7 Hollow-Core Section Properties (cont.)

Trade name Elematic® Equipment Manufacturer: Elematic Inc., Waukesha, Wisconsin with 2" topping Section Untopped \boldsymbol{y}_b depth x width in.4 in.4 lb/ft2 lb/ft2 in.2 in. in. 6" x 4'-0" 157 3.00 694 4.33 1557 66 8" x 4'-0" 196 3.97 1580 51 5.41 3024 76 10" x 4'-0" (5) 238 5.00 3042 6.49 5190 87 10" x 4'-0" (6) 249 5.00 3108 65 6.44 5280 90 12" x 4'-0" (4) 279 6.20 5104 7.90 8406 74 99 12" x 4'-0" (5) 274 6.00 5121 71 7.56 8134 96 16" x 4'-0" 346 8.30 11,339 91 10.2 16,883 116 20" x 4'-0" 501 10.3 24,087 133 12.0 33,073 158 H8" x 4'-0" 230 4.07 1667 5.34 3143 85 60 H12" x 4'-0" 307 6.00 5246 80 7.45 8393 105 8" x 8'-0" 404 4.00 3219 54 5.60 6475 79 10" x 8'-0" 549 5.00 6642 73 6.50 11,827 98 12" x 8'-0" 620 6.10 10,588 82 7.60 17,915 107 Note: All sections are not available from all producers. Check availability with regional manufacturers.